

(12) UK Patent Application (19) GB (11) 2 351 137 (13) A

(43) Date of A Publication 20.12.2000

(21) Application No 0013509.5

(22) Date of Filing 05.06.2000

(30) Priority Data

(31) 9913167

(32) 08.06.1999

(33) GB

(71) Applicant(s)

Beverley Elizabeth Alexandra Ward
79 Bristol Road, Edgbaston, BIRMINGHAM, B5 7TU,
United Kingdom

(72) Inventor(s)

Beverley Elizabeth Alexandra Ward

(74) Agent and/or Address for Service

Forrester Ketley & Co
Chamberlain House, Paradise Place, BIRMINGHAM,
B3 3HP, United Kingdom

(51) INT CL⁷

B65G 69/00

(52) UK CL (Edition R)

F2S SCF S704

(56) Documents Cited

EP 0547428 A1 WO 88/08403 A1 DE 001954812 A
FR 002686913 A US 5881414 A


(58) Field of Search

UK CL (Edition R) **B6E E28 , F2S SCF**
INT CL⁷ **B65G 69/00 , F16F 1/44**
Online: **WPI, EPODOC, JAPIO**

(54) Abstract Title

Vehicle loading bay

(57) The end wall (9) of a loading bay is protected by two bumpers (10a and 10b). Each bumper comprises a support member (14) extending a short distance from a flange (12), by which the support member may be bolted in position, and a resilient member (16) which may be mounted on the support member in a manner such as to be capable of limited vertical movement relative thereto. When a vehicle reverses into the bay, and strikes the resilient member (16), some at least of the load may be transmitted by the resilient member to the end wall (9). Additionally, in the event that a trailer is reversed against the bumpers vertical movement of the trailer which may take place will tend to cause vertical movement of the resilient members relative to their associated supporting members, reducing the tendency for damage to be caused.



GB 2 351 137 A

